

Material Safety Data Sheet

EPO PATCH & GROUT
QUICK IDENTIFIER (Clear and Pigmented)
Common Name: (Used on label and list)

May be used to comply with OSHA's Hazard Communication Standard,
29CFR 1910.1200. Standard must be consulted for specific requirements.

SECTION 1 -

Manufacturer's Name: DYNAMIS, INC.
Address: 415 E. VENICE AVE. Emergency Telephone No. 800/688-4005
City, State, ZIP: VENICE, FL 34292 Other Information Calls: 941/488-3999
Signature of Person Responsible for Preparation (Optional): Date Prepared: REVISED - 1/04

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY

** NOT IN CLEAR VERSION

Hazardous Component(s) (chemical & common name(s))	% (optional)	OSHA PEL	ACGIH TLV	Other Exposure Limits	CAS NO.
Tetraethylenepentamine		1	1	N/A	112-57-2
Tertiary Amine		N.I.F.	N.E.	N/A	TRADE SECRET
Phenol,4,4,-(1-methylethylidene)BIS-, polymer with (chloromethyl) oxirane common bisphenol A diglycidyl ether polymer.		N.E.	N.E.	N.E.	25068-38-6
Aromatic Petroleum Oil		N.E.	N.E.	N/A	68477-29-2
** Titanium Dioxide (See attached sheet for CAS numbers)		15mg/m3	10mg/m3		
** Tint Pigments					N/A

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The components of this product are contained on the chemical substance inventory list.

N.E. = NOT ESTABLISHED N.I.F. = NO INFORMATION FOUND

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	more than 200° F	Specific Gravity (H ₂ O = 1)	1.15	Vapor Pressure (mm Hg)	N.I.F.
	Vapor Density (Air = 1)				N.I.F.
Solubility in Water	Slight, in uncured state	Reactivity in Water			Unknown
Appearance and Odor	Clear or pigmented appearance, typical epoxy odor	Melting Point			Unknown

SECTION 4 - FIRE & EXPLOSION DATA

Flash Point	more than 200 F. C.	Method Used	PMCC	Flammable Limits in Air % by Volume	LEL Lower	N.I.F.	UEL Upper	N.I.F.
Auto-Ignition Temperature	N.I.F.	Extinguisher Media	CO ₂ , Foam, Dry Chemical					
Special Fire Fighting Procedures	Self-contained breathing apparatus.							

Unusual Fire and Explosion Hazards: Water not normally effective. Solid stream may spread fire.

Spray mist preferred.

SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)

Stability Unstable Conditions
Stable to Avoid

Incompatibility (Materials to Avoid) Acid Base - Component A

Avoid strong oxidizing agents - Component B

Hazardous

Decomposition Products Carbon monoxide, carbon dioxide, smoke & other possible unknown products.

Hazardous Polymerization May Occur Conditions
Will Not Occur to Avoid

SECTION 6 - HEALTH HAZARDS

1. Acute (Immediate) Dermatitis 2. Chronic (Delayed Effect) Skin irritant

Signs and Symptoms of Exposure Highly irritating to eyes. Defatting to skin. Rated as slight skin irritant. May be skin sensitizer.

Medical Conditions Generally Aggravated by Exposure Dermatitis

Chemical Listed as Carcinogen or Potential Carcinogen NONE National Toxicology Program Yes No I.A.R.C. Monographs Yes No OSHA Yes No

Emergency and First Aid Procedures This chemical is not considered to be carcinogenic by NTP, IARC or OSHA.

ROUTES OF ENTRY

- 1. Inhalation Remove to fresh air.
- 2. Eyes Flush with water. Medical attention as required.
- 3. Skin Wash with soap and water.
- 4. Ingestion Contact physician.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage Keep away from heat or open flame.

Other Precautions Persons who are chemically sensitive should not use this product.

Steps to be Taken in Case Material is Released or Spilled Pick up and discard appropriately.

Waste Disposal Methods (Consult federal, state, and local regulations) Burn in adequate incinerator or bury in an approved landfill.

SECTION 8 - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Respiratory Protection (Specify Type) Suitable for non-volatile epoxy compounds.

Ventilation Recommended Local Exhaust Recommended Mechanical (General) Special Other

Protective Gloves Required Eye Protection Recommended

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices Good hygiene habits. Clean clothing daily.

IMPORTANT
Do not leave any blank spaces. If required information is unavailable, unknown, or does not apply, so indicate.
CU-F1R Printed by Labelmaster, An American Labelmark Company, Chicago, IL 60646 (800) 621-5808

DYNAMIS, INC.
VENICE, FL

Page 3.

MATERIAL SAFETY DATA SHEET ADDENDUM

EPO PATCH & GROUT

Listed below are CAS Registry numbers for Titanium Dioxide:

1317-80-1
1317-70-0
1344-28-1
78-96-6
7784-30-7
1309-64-4
12030-97-6
77-99-6