

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 1 of 13

DYNA GLUE PART "B"

SECTION 1: Identification

Product Identifier

Product Name: DYNA GLUE PART "B"



Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: GEL ADHESIVE EPOXY CURING AGENT

Uses Advised Against: Any use other than recommended above.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Dynamis Epoxy Systems
415 E. Venice Avenue
Venice, FL 34285
941.488.3999
www.dcdynamis.com

Emergency Telephone Number:

United States

ChemTel
(888)-255-3924 (24 hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin corrosion, category 1A
Serious eye damage, category 1
Skin sensitization, category 1
Reproductive toxicity, category 2

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage
H318 Causes serious eye damage
H317 May cause an allergic skin reaction
H361 Suspected of damaging fertility or the unborn child

Precautionary Statements:

P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling
P280 Wear protective gloves/protective clothing/eye protection/face protection
P272 Contaminated work clothing must not be allowed out of the workplace

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 2 of 13

DYNA GLUE PART "B"

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER or doctor/physician

P321 Specific treatment (see Sections 4 - 8 of this SDS and any supplemental information on the product label)

P363 Wash contaminated clothing before reuse

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with all local, regional, state and federal regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 68082-29-1	C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	50-60
CAS Number: 84852-15-3	4-nonylphenol, branched	25-35
CAS Number: 140-31-8	1-Piperazineethanamine	5-15
CAS Number: 7631-86-9	Silicon dioxide (amorphous)	5-10
CAS Number: 112-24-3	Triethylenetetramine	1-3
CAS Number: 70969-70-9	2-ethylhexyl 3,5,5-trimethylhexanoate	<0.75

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance. Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 3 of 13

DYNA GLUE PART "B"

rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

After Eye Contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Exposure to decomposition products may result in adverse health effects. Serious effects may be delayed following exposure.

Delayed Symptoms and Effects:

The symptoms of inhalation exposure to thermal decomposition products may be delayed.

4-nonylphenol, branched is a suspected reproductive toxin. Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Immediate Medical Attention and Special Treatment

Specific Treatment:

This product is corrosive. Exposure by skin contact, eye contact and ingestion require urgent medical treatment.

In case of over-exposure, via inhalation, or inhalation exposure to thermal decomposition products seek prompt medical advice/attention.

Notes for the Doctor:

Treat symptomatically.

Symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 4 of 13

DYNA GLUE PART "B"

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Closed containers may rupture, due to pressure build up, when exposed to extreme heat. Thermal decomposition may produce irritating and toxic fumes including carbon oxides, nitrogen oxides and silicon oxides.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate the area of all non-essential personnel. Keep upwind to avoid inhaling smoke and fumes. Fight fire from a protected location. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only with adequate ventilation. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Keep away from open flame, hot surfaces, ignition sources and incompatible materials (see Section 10). Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Store in original container. Keep containers tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Store away from heat, open flames and other sources of ignition. Store away from incompatible materials (See Section 10). Use appropriate containment to avoid environmental contamination.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 5 of 13

DYNA GLUE PART "B"

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Silicon dioxide (amorphous)	7631-86-9	REL-TWA: 6 mg/m ³ (up to 10 hrs.)
	Silicon dioxide (amorphous)	7631-86-9	IDLH: 3000 mg/m ³
OSHA	Silicon dioxide (amorphous)	7631-86-9	8-Hour TWA-PEL: 2 mg/m ³
United States(California)	Silicon dioxide (amorphous)	7631-86-9	8-Hour TWA-PEL: 6 mg/m ³ (precipitated and gel)
	Silicon dioxide (amorphous)	7631-86-9	8-Hour TWA-PEL: 6 mg/m ³ (total dust)
	Silicon dioxide (amorphous)	7631-86-9	8-Hour TWA-PEL: 3 mg/m ³ (respirable dust)
WEEL	Triethylenetetramine	112-24-3	TWA: 1 ppm

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Use local exhaust, mechanical ventilation or additional engineering controls to maintain airborne concentrations below any occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protection Equipment

Eye and Face Protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

In case of insufficient ventilation, wear suitable respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a properly fitted, air-purifying or air-fed respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 6 of 13

DYNA GLUE PART "B"

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Translucent, Amber Gel
Odor	Ammonia
Odor threshold	Not determined or not available.
pH	Alkaline
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	400 °F (208 °C)
Flash point (closed cup)	388 °F
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.589 (water = 1)
Solubilities	Negligible in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other Information

VOC content	0 g/L
-------------	-------

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

Strong acids; Strong bases; Oxidizing agents

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 7 of 13

DYNA GLUE PART "B"

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Silicon dioxide (amorphous)	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: > 5.01 mg/L (4 h, dust)
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Triethylenetetramine	oral	LD50 Rat: 2500 mg/kg
	dermal	LD50 Rabbit: 850 mg/kg
4-nonylphenol, branched	oral	LD50 Rat: 1300 mg/kg
	dermal	LD50 Rabbit: 2037 mg/kg
1-Piperazineethanamine	oral	LD50 Rat: 1240 mg/kg
	dermal	LD50 Rabbit: 880 mg/kg
2-ethylhexyl 3,5,5-trimethylhexanoate	oral	LD50 Rat: >5000 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Causes skin irritation.
Triethylenetetramine	Causes severe skin burns.
4-nonylphenol, branched	Causes severe skin burns.
1-Piperazineethanamine	Causes severe skin burns.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Causes serious eye damage.
Triethylenetetramine	Causes serious eye damage.
4-nonylphenol, branched	Causes serious eye damage.
1-Piperazineethanamine	Causes serious eye damage.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 8 of 13

DYNA GLUE PART "B"

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Name	Result
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	May cause an allergic skin reaction.
Triethylenetetramine	May cause an allergic skin reaction.
1-Piperazineethanamine	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Silicon dioxide (amorphous)	Group 3

National Toxicology Program (NTP): None of the ingredients are listed.

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment:

Suspected of damaging fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
4-nonylphenol, branched	Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 9 of 13

DYNA GLUE PART "B"

Name	Result
2-ethylhexyl 3,5,5-trimethylhexanoate	May cause damage to organs (adrenal glands) through prolonged or repeated exposure (oral).

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

Inhalation; Ingestion; Skin contact; Eye contact

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

Refer to Section 4 of this SDS.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment:

Very toxic to aquatic life.

Product Data: No data available.

Substance Data:

Name	Result
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Fish LC50 Danio rerio: 7.07 mg/L (96 Hours)
	Aquatic Invertebrates EC50 Daphnia magna: 7.07 mg/L (48 Hours)
	Aquatic Plants ErC50 Pseudokirchneriella subcapitata: 4.34 mg/L (72 Hours)
4-nonylphenol, branched	Fish LC50 Lepomis macrochirus: 0.209 mg/L (96 Hours)
	Aquatic Invertebrates EC50 Daphnia magna: 0.0844 mg/L (48 Hours)
	Aquatic Plants EC50 Selenastrum capricornutum (green algae): 0.33 mg/L (72 Hours)

Chronic (Long-Term) Toxicity

Assessment:

Very toxic to aquatic life with long lasting effects.

Product Data: No data available.

Substance Data:

Name	Result
4-nonylphenol, branched	Fish NOEC Oncorhynchus mykiss: 0.006 mg/L (91 days)
	Aquatic Invertebrates NOEC Daphnia magna: 0.024 mg/L (21 days)
1-Piperazineethanamine	Aquatic Invertebrates EC50 Daphnia magna: 58 mg/L (48 hr)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Not readily biodegradable. 15% degradation after 28 days.
4-nonylphenol, branched	Inherently biodegradable (48.2% degradation after 35 days).

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 10 of 13

DYNA GLUE PART "B"

Name	Result
2-ethylhexyl 3,5,5-trimethylhexanoate	The substance is inherently biodegradable (58% degradation in 28 days).

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Silicon dioxide (amorphous)	BCF: 3.16 L/kg
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Low potential for bioaccumulation (BCF = 77.4 L/kg).
4-nonylphenol, branched	Low potential to bioaccumulate (BCF: 576 dimensionless [whole body]).
1-Piperazineethanamine	BCF: 2.8 - 6.3

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Silicon dioxide (amorphous)	Mobile (log Koc: 1.337)
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Immobile in soil.
4-nonylphenol, branched	Hardly mobile (Koc: 11,060 dimensionless).
1-Piperazineethanamine	Hardly Mobile (Log Koc: 4.57)

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Silicon dioxide (amorphous)	This substance is not PBT.
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	The substance is not PBT.
4-nonylphenol, branched	The substance is not PBT.
2-ethylhexyl 3,5,5-trimethylhexanoate	The substance is not PBT.

vPvB assessment:

Silicon dioxide (amorphous)	This substance is not vPvB.
C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	The substance is not vPvB.
4-nonylphenol, branched	The substance is not vPvB.
2-ethylhexyl 3,5,5-trimethylhexanoate	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 11 of 13

DYNA GLUE PART "B"

Disposal Methods:



It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

Contaminated packages:



Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, n.o.s. (Phenol, 4-nonyl-, branched, 1-Piperazineethanamine)
UN Transport Hazard Class(es)	8  
Packing Group	III
Environmental Hazards	Marine Pollutant (Phenol, 4-nonyl-, branched, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)
Special Precautions for User	None
Excepted Quantities	E1
Passenger Air/Rail	5 L
Cargo Aircraft Only	60 L
Stowage Category	A

International Maritime Dangerous Goods (IMDG)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, n.o.s. (Phenol, 4-nonyl-, branched, 1-Piperazineethanamine)
UN Transport Hazard Class(es)	8  
Packing Group	III
Environmental Hazards	Marine Pollutant (Phenol, 4-nonyl-, branched, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)
Special Precautions for User	None
Stowage Category	A
Excepted Quantities	5 L
Limited Quantity	E1

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, n.o.s. (Phenol, 4-nonyl-, branched, 1-Piperazineethanamine)



Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 12 of 13

DYNA GLUE PART "B"

UN Transport Hazard Class(es)	8	 
Packing Group	III	
Environmental Hazards	Marine Pollutant (Phenol, 4-nonyl-, branched, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)	
Special Precautions for User	None	
Excepted Quantities	E1	
Passenger and Cargo	5 L	
Cargo Aircraft Only	60 L	
Limited Quantity	5 L	

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5):

7631-86-9	Silicon dioxide (amorphous)	Not Listed
68082-29-1	C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Not Listed
112-24-3	Triethylenetetramine	Not Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Not Listed
70969-70-9	2-ethylhexyl 3,5,5-trimethylhexanoate	Not Listed

Export Notification under TSCA Section 12(b):

7631-86-9	Silicon dioxide (amorphous)	Not Listed
68082-29-1	C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Not Listed
112-24-3	Triethylenetetramine	Not Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Not Listed
70969-70-9	2-ethylhexyl 3,5,5-trimethylhexanoate	Not Listed

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

84852-15-3	4-nonylphenol, branched	Listed
------------	-------------------------	--------

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.21.2022

Page 13 of 13

DYNA GLUE PART "B"

Massachusetts Right to Know:

7631-86-9	Silicon dioxide (amorphous)	Listed
112-24-3	Triethylenetetramine	Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Listed

New Jersey Right to Know:

112-24-3	Triethylenetetramine	Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Listed

New York Right to Know:

7631-86-9	Silicon dioxide (amorphous)	Listed
112-24-3	Triethylenetetramine	Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Listed

Pennsylvania Right to Know:

7631-86-9	Silicon dioxide (amorphous)	Listed
112-24-3	Triethylenetetramine	Listed
84852-15-3	4-nonylphenol, branched	Listed
140-31-8	1-Piperazineethanamine	Listed

California Proposition 65: None of the ingredients are listed.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial Preparation Date: 02.21.2022

End of Safety Data Sheet