

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 1 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### SECTION 1: Identification

#### Product identifier

**Product name:** Epo Patch & Grout / Resurfacer LTC, Component "B"



#### Recommended use of the chemical and restrictions on use

**Recommended use:** Component B of Grout and Epoxy System

**Restrictions on use:** Any use other than recommended above.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

Dynamis Epoxy Systems

415 E. Venice Avenue

Venice, FL 34285

941.488.3999

www.dcdynamis.com

#### Emergency telephone number:

##### United States

ChemTel

(888)-255-3924 (24 hours)

### SECTION 2: Hazard(s) identification

**Classification in accordance with paragraph (d) (1)(i) of §1910.1200, GHS Revision 7 and certain provision of GHS Revision 8:**

#### Hazard Classification

Skin corrosion, category 1B

Serious eye damage, category 1

Skin sensitization, category 1

Carcinogenicity, category 1B

Aspiration hazard, category 1

#### Label elements

##### Pictogram(s):



**Signal Word:** Danger

##### Hazard statements:

H317 May cause an allergic skin reaction

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H350 May cause cancer

H304 May be fatal if swallowed and enters airways

##### Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dusts or mists.

P264 Wash any exposed skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 2 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center or doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P310 If swallowed: Immediately call a poison center or doctor.

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label).

P308+P313 If exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents and container in accordance with federal, state and local regulations.

**Hazards not otherwise classified:** None

**Supplemental label elements:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS Number: Trade Secret	Tetraethylenepentamine	30-50
CAS Number: Trade Secret	Modified Polyamines	30-50
CAS Number: 68477-29-2	Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	30-40

### Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR§1910.1200).

## SECTION 4: First-aid measures

### Description of first-aid measures

#### General notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest.

If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

#### After skin contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

#### After eye contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 3 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### After ingestion:

This product presents an aspiration hazard. If aspiration is suspected, seek emergency medical treatment. If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

### Most important symptoms/effects, acute and delayed

#### Acute symptoms and effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse. Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis. May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include shortness of breath, dry cough and irritation of the nose, eyes, lips, mouth and throat.

#### Delayed symptoms and effects:

Symptoms of pulmonary edema may be delayed.  
Chronic or repeated exposure to petroleum distillates may cause cancer.

### Indication of immediate medical attention and special treatment needed, if necessary

#### Immediate medical attention:

Not determined or not applicable.

#### Special treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.  
In case of skin contact, seek prompt medical attention while rinsing is continued.  
In case of ingestion, seek prompt medical attention.  
If aspiration is suspected, seek immediate medical attention.

#### Notes for the doctor:

Treat symptomatically. The symptoms of exposure may be delayed. Therefore, medical observation is indicated.

## SECTION 5: Fire-fighting measures

### Suitable (and unsuitable) extinguishing media

#### Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable extinguishing media:

Do not use water jet.

### Specific hazards arising from the chemical:

Thermal decomposition may produce irritation and toxic fumes/gases including carbon oxides and nitrogen oxides.

### Special protective equipment and precautions for fire-fighters

#### Special protective equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 4 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging.

### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.15.2018

Page 5 of 12

Revision date: 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	Tetraethylenepentamine	Trade Secret	8-Hour TWA: 5 mg/m <sup>3</sup> (1 ppm)
OSHA	Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	68477-29-2	8-Hour TWA-PEL: 2000 mg/m <sup>3</sup> ([500 ppm])
NIOSH	Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	68477-29-2	REL-TWA: 350 mg/m <sup>3</sup> (PETROLEUM DISTILLATES [up to 10 hr])
	Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	68477-29-2	Ceiling Limit: 1800 mg/m <sup>3</sup> (PETROLEUM DISTILLATES)
United States(California)	Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	68477-29-2	8-Hour TWA: 1600 mg/m <sup>3</sup> ([400 ppm] As Rubber solvent (Naphtha))

#### Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Not determined or not applicable.

#### Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

#### Individual protection measures, such as personal protective equipment

##### Eye and face protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

##### Skin protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

##### Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 6 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### General hygiene measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Color</b>	Amber
<b>Odor</b>	Slight Amine Odor
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flammability</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Flash point</b>	>210 °F
<b>Auto-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Solubility</b>	Slightly soluble in water in uncured state.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Density</b>	1.1
<b>Relative density</b>	Not determined or not available.
<b>Relative vapor density</b>	Not determined or not available.
<b>Particle characteristics</b>	Not determined or not available.

## SECTION 10: Stability and reactivity

### Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical stability:

Stable under recommended handling and storage conditions. Hazardous polymerization will not occur

### Possibility of hazardous reactions, including those associated with foreseeable emergencies:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

### Conditions to avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

### Incompatible materials:

Amine compounds under uncontrolled conditions; Strong acids; Bases; Oxidizing agents

### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 7 of 12

**Revision date:** 04.23.2025

**Epo Patch & Grout / Resurfacer LTC, Component "B"**

## SECTION 11: Toxicological information

### Acute toxicity

#### Assessment:

Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Modified Polyamines	oral	LD50 Rat: 1030 mg/kg
	inhalation	LC50 Rat: > 5.01 mg/L (4 hr [aerosol])
	dermal	LD50 Rat: >2000 mg/kg
Tetraethylenepentamine	dermal	LD50 Rabbit: 660 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg
Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
	inhalation	LC50 Rat: <5 mg/L (4 hr [aerosol])

### Skin corrosion/irritation

#### Assessment:

Causes severe skin burns and eye damage.

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	Causes severe skin burns.
Tetraethylenepentamine	Causes severe skin burns.
Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	Causes skin irritation.

### Serious eye damage/irritation

#### Assessment:

Causes serious eye damage.

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	Causes serious eye damage.
Tetraethylenepentamine	Causes serious eye damage.

### Respiratory or skin sensitization

#### Assessment:

May cause an allergic skin reaction.

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	May cause an allergic skin reaction.
Tetraethylenepentamine	May cause an allergic skin reaction.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 8 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### Carcinogenicity

**Assessment:**

May cause cancer.

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Distillates (petroleum), catalytic reformer fractionator residue, high-boiling		May cause cancer.

**International Agency for Research on Cancer (IARC):** None of the ingredients are listed.

**National Toxicology Program (NTP):** None of the ingredients are listed.

**OSHA Carcinogens:** Not applicable.

### Germ cell mutagenicity

**Assessment:**

Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:**

Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:**

Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Specific target organ toxicity (repeated exposure)

**Assessment:**

Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:**

May be fatal if swallowed and enters airways.

**Product data:** No data available.

**Substance data:**

Name	Result
Distillates (petroleum), catalytic reformer fractionator residue, high-boiling	May be fatal if swallowed and enters airways.

### Interactive effects:

No additional information.

### Information on likely routes of exposure:

Inhalation; Ingestion; Skin contact; Eye contact.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 9 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### Symptoms related to the physical, chemical and toxicological characteristics:

Refer to section 4 of this SDS.

### Other information:

No additional information.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

#### Assessment:

Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	Aquatic Plants EC50 <i>Desmodium subspicatus</i> : >50 mg/L (72 hr [growth rate])
	Fish LC50 <i>Leuciscus idus</i> : 110 mg/L (96 hr)
	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 23 mg/L (48 hr [mobility])
Tetraethylenepentamine	Fish LC50 <i>Poecilia reticulata</i> : 420 mg/L (96 hr)
	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 24.1 mg/L (48 hr [mobility])
	Aquatic Plants EC50 <i>Pseudokirchneriella subcapitata</i> : 2.1 mg/L (72 hr [growth rate])

### Chronic (Long-Term) Toxicity

#### Assessment:

Toxic to aquatic life with long lasting effects.

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	Aquatic Invertebrates NOEC <i>Daphnia magna</i> : 3 mg/L (21 d [reproduction])

### Persistence and Degradability

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	The substance is not readily biodegradable. 8% degradation in water, measured by DOC removal, after 28 days.
Tetraethylenepentamine	The substance is not readily biodegradable. <10 % degradation in water, after 28 days.

### Bioaccumulative potential

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	The substance is not expected to bioaccumulate (BCF: 76.22 L/kg, QSAR substance data, aquatic organisms: Fish).
Tetraethylenepentamine	Low potential for bioaccumulation. Log Pow: -3.42 to -2.60

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.15.2018

Page 10 of 12

Revision date: 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### Mobility in soil

**Product data:** No data available.

#### Substance data:

Name	Result
Modified Polyamines	The substance is moderately mobile, therefore, there is moderate potential for adsorption to soil and sediment (Koc: 928 at 25 °C, QSAR substance data).
Tetraethylenepentamine	The substance has a potential for adsorption to sediment particles and suspended organic matter based on data from analogous substance.

### Results of PBT and vPvB assessment

#### Product data:

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

#### Substance data:

##### PBT assessment:

Modified Polyamines	The substance is not PBT.
Tetraethylenepentamine	The substance is not PBT.

##### vPvB assessment:

Modified Polyamines	The substance is not vPvB.
Tetraethylenepentamine	The substance is not vPvB.

**Other adverse effects:** No additional adverse effects for the environment anticipated.

## SECTION 13: Disposal considerations

### Disposal methods:



It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport information

### United States Transportation of Dangerous Goods (49 CFR DOT)

UN number	2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s., (Tetraethylenepentamine)
UN transport hazard class(es)	8  
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Passenger Air/Rail	5 L
Cargo Aircraft Only	60 L
Stowage Category	A

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial Preparation Date: 02.15.2018

Page 11 of 12


Revision date: 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### International Maritime Dangerous Goods (IMDG) Code

UN Number	2735
UN Proper Shipping Name	AMINES, LIQUID, CORROSIVE, N.O.S., (Tetraethylenepentamine)
UN Transport Hazard Class(es)	8 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
EmS Number	F-A, S-B
Stowage Category	A
Excepted Quantities	E1
Limited Quantity	5 L

### International Air Transport Association (IATA) Dangerous Goods Regulations (DGR)

UN Number	2735
UN Proper Shipping Name	Amines, liquid, corrosive, n.o.s., (Tetraethylenepentamine)
UN Transport Hazard Class(es)	8 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
ERG Code	8L
Excepted Quantities	E1
Passenger and Cargo	5 L
Cargo Aircraft Only	60 L
Limited Quantity	1 L

### Transport in Bulk according to IMO Instruments

IMO hazard class	Not applicable
Environmental hazards	Not applicable
Material hazardous only in bulk	Not applicable

## SECTION 15: Regulatory information

### United States Regulations

**Inventory Listing (TSCA):** All ingredients are listed-active or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 Extremely Hazardous Substances:** None of the ingredients are listed.

**SARA Section 313 Toxic Chemicals:** None of the ingredients are listed.

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 02.15.2018

Page 12 of 12

**Revision date:** 04.23.2025

## Epo Patch & Grout / Resurfacer LTC, Component "B"

### Massachusetts Right to Know:

Trade Secret	Tetraethylenepentamine	Listed
--------------	------------------------	--------

### New Jersey Right to Know:

Trade Secret	Modified Polyamines	Listed
Trade Secret	Tetraethylenepentamine	Listed

### New York Right to Know:

Trade Secret	Modified Polyamines	Listed
Trade Secret	Tetraethylenepentamine	Listed

### Pennsylvania Right to Know:

Trade Secret	Tetraethylenepentamine	Listed
--------------	------------------------	--------

**California Proposition 65:** None of the ingredients are listed.

**Additional information:** No additional information.

## SECTION 16: Other information

### Disclaimer:

This product has been classified in accordance with paragraph (d) (1)(i) of 1910.1200, GHS Revision 7 and certain provision of GHS Revision 8. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**Initial Preparation Date:** 02.15.2018

**Revision date:** 04.23.2025

**End of Safety Data Sheet**